



TX502

Valve actuator KNX with temperature control + 2 reserve inputs

Technical properties

Architecture

Bus system	EIB
Fixing mode	Clamping

Functions

Function	with valve protection function ; Functions summer operation and forced mode
Operating mode	Operating modes: comfort, standby, night lowering, frost/heat protected

Configuration

Pre-assembled	pre-assembled, with cable
---------------	---------------------------

Controls and indicators

Button / push-button	with programming button and red programming LED
----------------------	---

Connectivity

Binary inputs	with 2 independent binary inputs
---------------	----------------------------------

Voltage

Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

Electric current

Bus consumption	10 mA
Bus current consumption (data transfer)	10 mA
Number of entry circuits	2

Dimensions

Depth of installed product	65 mm
Height of installed product	84 mm
Width of installed product	50 mm

Tripping

Run time	20 s/mm
----------	---------

Measurement

Reduced temperature setting	comfort temperature -2 to -8°C
-----------------------------	--------------------------------

Materials

Colour	white
RAL colour	RAL 9010 - Pure white

Mecanic features

Maximum controller stroke	6 mn
---------------------------	------

LED control

LED	with 5 LEDs for display of valve stroke
-----	---

Connection

Type of connection to the bus	TG008 connector
-------------------------------	-----------------

Bus coupling unit	with integral bus coupling unit
-------------------	---------------------------------

Bus connection	bus connection via connecting terminal
----------------	--

Cable

Pre-assembled cable	≈ 1 m
---------------------	-------

Settings

Supported configuration modes	system, easy
-------------------------------	--------------

Comfort temperature setpoint	10 / 30 °C
------------------------------	------------

Set force	>120 N
-----------	--------

Equipment

Detection of valve limit stops	Automatic
--------------------------------	-----------

Heating	for heating or cooling mode
---------	-----------------------------

Control	for continuous PI control
---------	---------------------------

Safety

Frost protection temperature setting	3 / 10 °C
--------------------------------------	-----------

Use conditions

Operating temperature	0...50 °C
-----------------------	-----------

Storage/transport temperature	-20...70 °C
-------------------------------	-------------

temperatur

Standby temperature setpoint	comfort temperature -0.5 to 4°C
------------------------------	---------------------------------

Identification

Main design line	KNX
------------------	-----