


TYA608A



**Output module 8x 4A /230V~, KNX**

**Technical properties**

**Architecture**

Bus system	yes
Fixing mode	REG

**Functions**

Multi-phase mode	suitable to switch different external conductors
Function	with positioning function for blind and lamella position ; with safety functions e.g. for wind, rain, alarm ; with sun shade function
Switching	for switching, e.g. of 8 independent loads or activation of 4 drives
Operating mode	any combined operation from drive and switching functions possible

**Configuration**

Number of modules	6
-------------------	---

**Controls and indicators**

Indicator lamp	yes
Operation	Manual operation can be activated via selection switch, thereby deactivation of the KNX function ; manual operation per channel using button (single-area operation)
Indication / display	status LED integrated in the manual operation button
Manual selection switches / push-buttons	manual operation buttons for on/off (up/down) and bus function on/off per channel/device
Button / push-button	with illuminated programming button

**Main electrical features**

Rated current	4 A
---------------	-----

**Voltage**

Operating voltage over bus	21...32 V DC
Output voltage	230 V~
System supply voltage	30V DC via bus

**Electric current**

Bus current consumption (data transfer)	15 mA
Bus current consumption (idle)	9 mA
Number of entry circuits	0
Maximum through current	4 A
Switching current at $\cos \varphi = 0.8$	max. 4 A

**Dimensions**

Depth	65 mm
Width of rail mounted device (RMD)	6 modules
Height	90 mm

**Power**

Max. power with electronic transfo.	800 W
Total power loss under IN	2 W
Output power	800 W
Conventional transformers	800 VA
Electronic transformers	800 W

**Materials**

Colour	light grey
--------	------------

**Lighting control**

Fluorescent lamps with electrical ballast (EB)	12 x 36 W
- uncompensated	800 W

**Fluorescent bulbs control**

Energy-saving lamps	6 x 23 W
Power lighting fluo lamps	6x23W
Max. power fluo. duo lamp comp. series	12 x 36 W

**LED control**

Max number of LED/CFL lamps	6
230V LED lamps	6 x 23 W
Power LED	72 W
LED	Status LED integrated in manual operation button

**Incandescent bulbs control**

Max. power with incandescent lamps	800 W
230 V incandescent lamps	800 W
230 V halogen lamps	800 W
230 V incandescent lamps and halogen lamps	800 W

**Connection**

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
Conductor cross-section (flexible)	0.75...2.5 mm <sup>2</sup>
Conductor cross-section (rigid)	0.75...2.5 mm <sup>2</sup>
Type of contacts	8NO
Bus coupling unit	with integral bus coupling unit
Type of connection	with QuickConnect plug-in terminals
Bus connection	bus connection via connecting terminal
Type of connection	quick connect

**Settings**

Supported configuration modes	system
Setting	switching time on change of direction adjustable
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Equipment</b>	
Modular expandability	No
<b>Use</b>	
Differentiation characteristic 3 - Sales	with plug-in terminals
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	
Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C
<b>Identification</b>	
Main design line	KNX