



SPK602

Surge protection for ADSL DIN-Rail

Technical properties

Installation, mounting

Mounting on	DIN rail
Nominal tightening torque	0.5 - 0.5 Nm

Standards

Requirement class IEC 61643	C1, C2, C3, D1, B2
-----------------------------	--------------------

Capacity

Number of modules	1
-------------------	---

Voltage

Rated operational voltage Ue	130 - 130 V
Continuous operating voltage Uc according to IEC 61643-1	185 V
Voltage protection level Up according to IEC 61643-1	0.30 kV

Electric current

Nominal discharge current In 8 - 20 μ s C2 IEC 61643	10 kA
Lightning impulse current Iimp (10/350 μ s) IEC 61643 L-N(PEN)/ N-PE	1 kA
Max. discharge (Imax) L-N(PEN)/ N-PE	10 kA

Dimensions

Height	90 mm
Width	17.70 mm
Depth	65.5 mm

Use conditions

Operating temperature	-40 - 85 °C
-----------------------	-------------

Equipment

With remote signalling contact	Yes
--------------------------------	-----

Connection

Cross-section of input and output with screws, for flexible conductors	0.2 - 2.5 mm ²
Cross-section of input and output with screws, for massive conductors	0.2 - 4 mm ²