



16216074

Rocker w. 2 lenses attached and imprinted light symbol, Q.x, alu velvety, lacq.

Technical properties

Controls and indicators

| | |
|----------------------------------|---|
| Push-buttons | also for KNX applications: push-button, 1gang, and group push-button, 1gang |
| Rocker switch/rocker push-button | for rocker push-buttons, for change-over/intermediate switch |

Materials

| | |
|------------------------|----------------------------|
| Colour | aluminium |
| Colour | aluminium optics |
| RAL colour | RAL 9006 - White aluminium |
| Material / workmanship | lacquered |
| Material | duroplastic |
| Surface appearance | velvety |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Equipment

| | |
|----------|-------------------------------------|
| Lighting | for lighting and monitoring circuit |
|----------|-------------------------------------|

Use cases

| | |
|-------------|---------------|
| Application | Light control |
|-------------|---------------|

Use

| | |
|--|------|
| Differentiation characteristic 2 - Sales | Lens |
|--|------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | No |

Identification

| | |
|--------------------------|---|
| Application, usage | Light control, Flush-mounted wet-room installation, KNX - operating systems |
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

| | |
|-------------------|---|
| Special note text | The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons. |
|-------------------|---|