



16216079

Rocker imprinted symbol for light, lens, Q.1/Q.3, p. white velvety

Technical properties

_	_	_		
Con	trole	and	indi	cators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang	
Rocker switch/rocker push-button	for rocker push-buttons ; for change- over/intermediate switch	
Materials		
Colour of design line	polar white	
Colour	white	
RAL colour	RAL 9010 - Pure white	
Surface appearance	velvety	
Installation, mounting		
Installation mode	clamp fastening	
Equipment		
Lighting	for lighting and monitoring circuit	
Use cases		
Application	Light control	
Use		
Differentiation characteristic 2 - Sales	Lens	
Safety		
REACH conform	Yes	
RoHS conform	Yes	
Halogen free	Yes	
Identification		
Application, usage	Light control ; Flush-mounted wet-room installation	
Main design line	Berker Q.1/Q.3/Q.7/Q.9	
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9	
Instructions		
Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.	