



16402045

Relay switch centre plate for hotel card, R.1/R.3, black glossy

Technical properties

Architecture

Number of keys	0
----------------	---

Configuration

Switch mode	1pole
-------------	-------

Antibacterial treatment	No
-------------------------	----

Main electrical features

Nominal voltage	230 V
-----------------	-------

Rated voltage	230 V AC
---------------	----------

Frequency	50/60 Hz
-----------	----------

Electric current

Inductive load at $\cos \varphi = 0.6$	max. 6 A
----------------------------------------	----------

Switching current	10 A / 230 V AC1
-------------------	------------------

Dimensions

Depth	57.3 mm
-------	---------

Insertion depth	32 mm
-----------------	-------

Card width	max. 55 mm
------------	------------

Card thickness	0.8...1.2 mm
----------------	--------------

Height	69.5 mm
--------	---------

Width	69.5 mm
-------	---------

Power

Conventional transformers	1500 VA
---------------------------	---------

Electronic transformers	1500 W
-------------------------	--------

Power consumption	< 0.2 W
-------------------	---------

Materials

Colour of design line	black
-----------------------	-------

Colour	black
--------	-------

Surface appearance	glossy
--------------------	--------

Fluorescent bulbs control

Compact fluorescent lamps	500 W
---------------------------	-------

Fluorescent lamps in duo circuit	1500 W
----------------------------------	--------

LED control

LED	illuminated with blue LED if hotel card is not inserted
-----	---------------------------------------------------------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps

1500 W

Installation, mounting

Installation mode with spreader claws

ConnectionScrew terminals (max.) 2 x 2,5 mm²

Type of connection with screw-in lift terminals

Settings

Delay time incrementally adjustable 0, 15, 30, 60 s

Setting with potentiometer for incremental adjustment of delay time

Equipment

Lighting for illumination

Potential-free with potential-free contact

Use cases

Application Light control ; Hotel application

Safety

REACH conform No

RoHS conform Yes

Halogen free No

Use conditions

Operating temperature -5...50 °C

Storage/transport temperature -25...70 °C (storage at > 45°C reduces the service life)

Identification

Application, usage Light control

Main design line Berker R.1/R.3/R.8

Secondary design line(s) Berker R.1 ; Berker R.3