



16406099

Relay switch centre plate for hotel card, Q.x, p. white velvety

Technical properties

Architecture

Number of keys	0
Fixing mode	flush-mounting

Configuration

Switch mode	1pole
Antibacterial treatment	No

Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC
Frequency	50/60 Hz

Electric current

Inductive load at $\cos \varphi = 0.6$	max. 6 A
Switching current	10 A / 230 V AC1

Dimensions

Depth	57.3 mm
Insertion depth	32 mm
Card width	max. 55 mm
Card thickness	0.8...1.2 mm
Height	71 mm
Width	71 mm

Power

Conventional transformers	1500 VA
Electronic transformers	1500 W

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Surface appearance	velvety

Fluorescent bulbs control

Compact fluorescent lamps	500 W
Fluorescent lamps in duo circuit	1500 W

LED control	
LED	illuminated with blue LED if hotel card is not inserted
Incandescent bulbs control	
230 V incandescent lamps and halogen lamps	1500 W
Installation, mounting	
Installation mode	with spreader claws
Connection	
Screw terminals (max.)	2 x 2,5 mm ²
Type of connection	with screw-in lift terminals
Settings	
Delay time incrementally adjustable	0, 15, 30, 60 s
Setting	with potentiometer for incremental adjustment of delay time
Equipment	
Lighting	for illumination
Potential-free	with potential-free contact
Use cases	
Application	Light control, Hotel application
Safety	
Protection index IP	IP20
REACH conform	No
RoHS conform	Yes
Halogen free	No
Use conditions	
Operating temperature	-5...50 °C
Storage/transport temperature	-25...70 °C (storage at > 45°C reduces the service life)
Identification	
Application, usage	Light control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9