



16512049

**Rocker f.accessible const., tactile symb. f.light, clearlens,R.1/R.3,p.white gl.**

#### Technical properties

#### Controls and indicators

|                                  |   |
|----------------------------------|---|
| Push-buttons                     | also for KNX applications: push-button, 1gang |
| Rocker switch/rocker push-button | for illuminated rocker push-buttons           |

#### Materials

|                       |                       |
|-----------------------|-----------------------|
| Colour of labelling   | 105,105,105           |
| Colour of design line | polar white           |
| Colour                | white                 |
| RAL colour            | RAL 9010 - Pure white |
| Material for printing | ASA polar white       |
| Surface appearance    | glossy                |

#### Installation, mounting

|                   |                 |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

#### Settings

|                   |          |
|-------------------|----------|
| Shading parameter | R1_biały |
| Laser parameter   | R1_weiß  |

#### Equipment

|                       |                                     |
|-----------------------|-------------------------------------|
| Type of configuration | Laserdruck                          |
| Lighting              | for lighting and monitoring circuit |

#### Use cases

|                       |  |
|-----------------------|--|
| Barrier-free building | based on DIN 18040                       |
| Application           | Barrier-free application ; Light control |

#### Use

|  |                               |
|--|-------------------------------|
| Differentiation characteristic 1 - Sales | with tactile symbol for light |
| Differentiation characteristic 2 - Sales | with clear lens               |

#### Safety

|               |     |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform  | Yes |
| Halogen free  | Yes |

#### Identification

|                          |   |
|--------------------------|---|
| Application, usage       | Flush-mounted wet-room installation ; Light control |
| Main design line         | Berker R.1/R.3/R.8                                  |
| Secondary design line(s) | Berker R.1 ; Berker R.3 ; Berker R.8                |

Special note text

The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.