



16516069

**Rocker f.accessible const., tactile symb. f.door, redlens, Q.x,p.white velv.**

#### Technical properties

#### Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang
Rocker switch/rocker push-button	for illuminated rocker push-buttons

#### Materials

Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Surface appearance	velvety

#### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

#### Equipment

Lighting	for lighting and monitoring circuit
----------	-------------------------------------

#### Use cases

Barrier-free building	based on DIN 18040
Application	Barrier-free application ; Light control

#### Use

Differentiation characteristic 1 - Sales	with tactile symbol for door
Differentiation characteristic 2 - Sales	with orange lens

#### Safety

REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes

#### Identification

Application, usage	Flush-mounted wet-room installation ; Light control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9

#### Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
-------------------	---