



16517309

Rocker f. accessible const., tactile symbol f. door, redlens , K.1, p.white gl.

Technical properties

Controls and indicators

| | |
|----------------------------------|---|
| Push-buttons | also for KNX applications: push-button, 1gang |
| Rocker switch/rocker push-button | for illuminated rocker push-buttons |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Surface appearance | glossy |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Use cases

| | |
|-----------------------|--|
| Barrier-free building | based on DIN 18040 |
| Application | Barrier-free application ; Light control |

Use

| | |
|--|------------------------------|
| Differentiation characteristic 1 - Sales | with tactile symbol for door |
| Differentiation characteristic 2 - Sales | red lens |

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | Yes |

Identification

| | |
|--------------------|---|
| Application, usage | Flush-mounted wet-room installation ; Light control |
| Main design line | Berker K.1 |

Instructions

| | |
|-------------------|---|
| Special note text | The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons. |
|-------------------|---|