



167504

Neon lamp unit N terminal, light control, orange

Technical properties

Controls and indicators

Rocker switch/rocker push-button	for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808, for change-over/intermediate switch and on/off switch, 2-pole, 10 AX
----------------------------------	--

Main electrical features

Rated current	0.4 mA
---------------	--------

Dimensions

Insertion depth	13 mm
-----------------	-------

Materials

Colour independent of design lines	orange
------------------------------------	--------

Equipment

Lighting	for lighting and monitoring circuit
Combination rocker switches/rocker push-buttons	for series switch illuminated

Use cases

Application	Light control
-------------	---------------

Safety

REACH conform	Yes
RoHS conform	Yes

Identification

Application, usage	Light control
Main design line	Light control
Secondary design line(s)	Light control, ACCESSORIES

Instructions

Special note text	Refer to the overview for the matching flush-mounted inserts. ; these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").
Information text	When several neon lamp units are used, the lamp current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA neon lamp current) in parallel with the coil.