



28807009

Radio Touch, with loudspeaker, K.1, polar white glossy

Technical properties

| Functions | |
|-----------------------------------|---|
| Function | volume control, countdown, sleep timer, alarm clock with snooze function |
| Compatibility | |
| For loudspeakers | per channel $48~\Omega$ |
| Controls and indicators | |
| Operation | operation via sensor areas of the touch display |
| Indication / display | Time and date display, illuminated touch graphics display |
| Connectivity | |
| Reception / transmission | stereo FM radio with RDS display |
| Inputs | external audio input AUX IN |
| Main electrical features | |
| Frequency | 50/60 Hz |
| Dimensions | |
| Insertion depth | 33 mm |
| Dimensions of display (W x H) | 35 x 28 mm |
| Height | 70.8 mm |
| Width | 141.6 mm |
| Frequency | |
| Frequency range (radio reception) | 87.5108 MHz |
| Measurement | |
| Extension unit input | extension unit input for separate on/off switching |
| Materials | |
| Colour of design line | polar white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | Mixed materials |
| Installation, mounting | |
| Installation mode | single and combination mounting, screw fastening via supporting plate |
| Connection | |
| Conductor cross-section | max. 2.5 mm² |

| Conductor cross-section (loudspeakers) | max. 1.5 mm² |
|--|---|
| Type of connection | with screw terminals |
| Connection | with 2 loudspeaker connections |
| Scope of delivery | |
| Component | with one loudspeaker |
| Equipment | |
| Cylinder | 8 station memory, non-volatile, switch-on with last station |
| Use | |
| Differentiation characteristic 3 - Sales | with loudspeaker |
| Identification | |
| Application, usage | Communication technology |

Berker K.1

Main design line