



High definition soc. out., K.5, al., matt, lacq.

Technical properties

| - Common properties | |
|----------------------------|---|
| Architecture | |
| Number of poles | 19pole |
| Connectivity | |
| Outlet | with straight outlet |
| Connectors / jacks | with HDMI double socket, type A, supports HDMI technology (V 2.1) |
| Dimensions | |
| Insertion depth | 16.8 mm |
| Frequency | |
| Frequency range (vertical) | 5085 Hz |
| Screen | |
| Resolution | max. 1920 x 1080 px |
| Storage | |
| Transmission rate | max. 8.16 Gbit/s |
| Materials | |
| Colour of design line | aluminium |
| Material / workmanship | lacquered |
| Surface appearance | matt |
| Material / surface | gold-plated contacts |
| Installation, mounting | |
| Installation mode | without spreader claws ; for screw fastening |
| Safety | |
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | No |
| Identification | |
| Application, usage | Communication technology |
| Main design line | Berker K.5 |

Instructions

Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74; For the connection of digital devices for transmission of high-resolution audio and video signals, such as satellite receivers and DVD players, to LCD or plasma screens.; Observe the instructions of the cable and device manufacturers for maximum HDMI cable lengths!; Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092

Information text