



High definition soc. out. 90° plug connection, R.1/R.3, p. white glossy

Technical properties

Architecture	
Number of poles	19pole
Connectivity	
Outlet	with straight outlet
Connectors / jacks	with HDMI double socket, type A, supports HDMI technology (V 2.1)
Dimensions	
Insertion depth	41 mm
Frequency	
Frequency range (vertical)	5085 Hz
Screen	
Resolution	max. 1920 x 1080 px
Storage	
Transmission rate	max. 8.16 Gbit/s
Materials	
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Material for printing	ASA polar white
Material / surface	gold-plated contacts
Installation, mounting	
Installation mode	without spreader claws, for screw fastening
Settings	
Shading parameter	R1_biały
Laser parameter	R1_weiß
Equipment	
Type of configuration	Laserdruck
Identification	
Application, usage	Communication technology
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Porker D 1 Porker D 2 Porker D 9

Berker R.1, Berker R.3, Berker R.8

Secondary design line(s)

Instructions

Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74; For the connection of digital devices for transmission of high-resolution audio and video signals, such as satellite receivers and DVD players, to LCD or plasma screens.; Observe the instructions of the cable and device manufacturers for maximum HDMI cable lengths!; Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092

Information text