



382610

Change-over switch 2pole for lock cylinders, light control

Technical properties

Architecture

| | |
|----------------------|------------------|
| Type of control unit | Key |
| Fixing mode | surface-mounting |

Configuration

| | |
|-------------------------|------------------------|
| Switch mode | 2-pole off/change-over |
| Antibacterial treatment | No |

Compatibility

| | |
|-------------------------|----|
| IFTTT support available | No |
|-------------------------|----|

Controls and indicators

| | |
|--------------|----|
| Push-buttons | No |
|--------------|----|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|-------------------|---|
| Switching current | 16 AX (200 W Self Ballasted Lamp (SBL)) |
|-------------------|---|

Dimensions

| | |
|--------|---------|
| Depth | 40.1 mm |
| Height | 70.8 mm |
| Width | 70.8 mm |

Materials

| | |
|--------------------|---------------|
| Material | Plastic/metal |
| Surface appearance | matt |

Installation, mounting

| | |
|-------------------|---|
| Installation mode | without spreader claws, for screw fastening |
|-------------------|---|

Connection

| | |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1 |
| Type of connection | with screw terminals |
| Type of connection | Screw connection |

Equipment

| | |
|----------|--|
| Lighting | without lighting (cannot be illuminated) |
|----------|--|

| | |
|------------------------|--|
| Closures / Key systems | for master-key systems |
| Lock cylinder | for lock cylinder |
| Heating switch | No |
| Use cases | |
| Application | Blind control, Light control |
| Safety | |
| Protection index IP | IP20 |
| REACH conform | Yes |
| RoHS conform | Yes |
| Identification | |
| Application, usage | Light control |
| Main design line | Light control |
| Instructions | |
| Information text | for standardised profile half-cylinder lock, 40 mm |