



382610

Change-over switch 2pole for lock cylinders, light control

Technical properties

Architecture

Type of control unit	Key
----------------------	-----

Configuration

Switch mode	2-pole off/change-over
Antibacterial treatment	No

Compatibility

IFTTT support available	No
-------------------------	----

Controls and indicators

Push-buttons	No
--------------	----

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	16 AX (200 W Self Ballasted Lamp (SBL))
-------------------	---

Dimensions

Depth	40.1 mm
Height	70.8 mm
Width	70.8 mm

Materials

Surface appearance	matt
--------------------	------

Installation, mounting

Installation mode	without spreader claws ; for screw fastening
-------------------	--

Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	with screw terminals
Type of connection	Screw connection

Equipment

Lighting	without lighting (cannot be illuminated)
Closures / Key systems	for master-key systems
Lock cylinder	for lock cylinder

Heating switch

No

Use cases

Application

Blind control ; Light control

Safety

REACH conform

Yes

RoHS conform

Yes

Identification

Application, usage

Light control

Main design line

Light control

Instructions

Information text

for standardised profile half-cylinder lock, 40 mm