



383620

**Change-over switch f. lock cylinders, earth contact, splash-prot. flush-mtd IP44**

**Technical properties**

**Architecture**

Type of control unit Key

**Configuration**

Switch mode Off/change-over

Antibacterial treatment No

**Compatibility**

IFTTT support available No

**Controls and indicators**

Push-buttons No

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

**Electric current**

Switching current 16 AX (200 W Self Ballasted Lamp (SBL))

**Dimensions**

Depth 40.2 mm

Height 71 mm

Width 71 mm

**Installation, mounting**

Installation mode without spreader claws ; for screw fastening

**Connection**

Connection terminals according to IEC 60669-1

Connection terminals according to VDE 0632-1

Type of connection with screw terminals

Type of connection Screw connection

**Equipment**

Closures / Key systems for master-key systems

Lock cylinder for lock cylinder

Heating switch No

**Use cases**

Application Blind control ; Light control

**Use**

---

Differentiation characteristic 2 - Sales

with earth contact

**Safety**

---

Protection index IP

IP44

**Identification**

---

Application, usage

Light control

---

Main design line

Splash-protected flush-mounted IP44

**Instructions**

---

Information text

for standardised profile half-cylinder lock, 40 mm