

≈ 2 lx



41097004

SCHUKO soc.out. LED orient.,enhncd contact prot.,screw-in lift ,K5,steel,lacq

Technical properties

Architecture	
Design	according to DIN 49440
Fixing mode	flush-mounting
Configuration	
Number of modules	1
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Electric current	
Rated current	16 A
Dimensions	
Insertion depth	32 mm
Power	
Power consumption	0.25 W/0.35 VA
Cover, door	
Cover	Central cover plate
Detection	
Sensor	integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness
Materials	
Colour of design line	stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt
Lighting control	
Switch-off brightness	≈ 4 lx

Switch-on brightness

Light intensity (white) 0.2 cd

LED control

LED white LED light, long service life of the LED

Installation, mounting

Installation mode with spreader claws

Connection

Conductor cross-section (rigid) 2.5 Connection terminals according to IEC 60884-1 according to VDE 0620-1 Connection terminals

Type of connection with screw-in lift terminals

Cable

through-wiring possible, therefore also ideal for

Wiring retrofitting

Equipment

additional benefit by combination of a socket outlet Lighting with an orientation light

Use

Differentiation characteristic 2 - Sales enhanced contact protection

Differentiation characteristic 3 - Sales Screw-in lift terminals

Safety

IK protection code against mecanical 05 impacts Protection index IP IP20 REACH conform Yes

RoHS conform Yes Halogen free No

Protection Enhanced contact protection

With enhanced contact protection Yes

Identification

Main design line Berker K.5

Instructions

Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not

Information text compatible with the standard socket outlets.