



41108913

**SCHUKO soc.out. LED+"SV" impr.,labfield,enhncd contact prot., S1/B3/7een**

**Technical properties**

**Architecture**

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

**Configuration**

|                   |   |
|-------------------|---|
| Number of modules | 1 |
|-------------------|---|

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Electric current**

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

**Dimensions**

|   |       |
|---|-------|
| Insertion depth                         | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

**Cover, door**

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

**Materials**

|                              |                       |
|------------------------------|-----------------------|
| Design lines special colours | green                 |
| Colour                       | green                 |
| Colour                       | green                 |
| RAL colour                   | RAL 6029 - Mint green |
| Material                     | duroplastic           |
| Surface appearance           | glossy                |
| Metallic colour              | No                    |

**Installation, mounting**

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

**Connection**

|                      |                              |
|----------------------|------------------------------|
| Connection terminals | according to VDE 0620-1      |
| Type of connection   | with screw-in lift terminals |

**Use**

|  |                      |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
|--|----------------------|

---

**Standards**

Execution SV, ZSV

according to VDE 0100-710

---

**Safety**

IK protection code against mechanical impacts

IK02

Protection index IP

IP20

Protection

Enhanced contact protection

With enhanced contact protection

Yes

---

**Identification**

Main design line

Berker S.1/B.3/B.7

Secondary design line(s)

Berker S.1 ; Berker B.3 ; Berker B.7

---

**Instructions**

Information text

Labelling field height arranged for P-touch strips 6 mm. ; Insert colour-coded.