



41527109

## SCHUKO socket outlet with overvoltage protection, K.1, polar white glossy

### Technical properties

#### Architecture

Design according to DIN 49440

#### Configuration

Number of modules 1

#### Controls and indicators

Message with acoustic fault signal

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

#### Voltage

Overvoltage protection according to EN 61643 and VDE 0675-6-11

#### Electric current

Rated current 16 A

#### Dimensions

Insertion depth 32 mm

#### Cover, door

Cover Central cover plate

#### Materials

Colour of design line polar white

Colour white

RAL colour RAL 9010 - Pure white

Surface appearance glossy

#### Installation, mounting

Installation mode with spreader claws

#### Connection

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1

Type of connection with screw terminals

#### Equipment

**Use cases**

---

Application	Security and safety systems
-------------	-----------------------------

**Use**

---

Differentiation characteristic 1 - Sales	with labelling field
------------------------------------------	----------------------

---

Differentiation characteristic 3 - Sales	Screw terminals
------------------------------------------	-----------------

**Safety**

---

IK protection code against mechanical impacts	07
-----------------------------------------------	----

---

Protection	without enhanced contact protection
------------	-------------------------------------

---

With enhanced contact protection	No
----------------------------------	----

**Identification**

---

Main design line	Berker K.1
------------------	------------

**Instructions**

---

Information text	Labelling field height arranged for P-touch strips 6 mm.
------------------	----------------------------------------------------------