


with spreader claws



505601

Push-button insert for hotel card switch cover, Module inserts

Technical properties

Compatibility

Installation, mounting

Installation mode

Safety

| Architecture | |
|----------------------|------------|
| Type of control unit | Hotel card |
| Number of keys | 0 |
| Configuration | |

| Switch mode | change-over contact, usable as NC or NO |
|-------------------------|---|
| Antibacterial treatment | No |
| | |

| IFTTT support available | No |
|--------------------------|----|
| Main electrical features | |

| Nominal voltage | 250 V |
|-----------------|----------|
| Rated voltage | 250 V AC |

| Electric current | | |
|---------------------------|-----|--|
| Momentary-contact current | 2 A | |
| | | |

| Dimensions | |
|-----------------|---------|
| Depth | 41 mm |
| Insertion depth | 31.2 mm |
| Height | 71 mm |
| Width | 71 mm |

| Insertion depth | 31.2 mm |
|-----------------|---------|
| Height | 71 mm |
| Width | 71 mm |

| Connection | |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1 |
| Type of connection | with plug-in terminals |

| | _ |
|-------------------------|---|
| Connection terminals | according to VDE 0632-1 |
| Type of connection | with plug-in terminals |
| Equipment | |
| Quantity of NC contacts | 1 |
| Quantity of NO contacts | 1 |
| Lighting | can be illuminated using neon and glow lamp unit with N-terminal ; for lighting and monitoring circuit |
| Use cases | |
| Application | Light control ; Hotel application |

| REACH conform | No |
|--------------------|---------------|
| RoHS conform | Yes |
| Halogen free | Yes |
| Identification | |
| Application, usage | Light control |
| Main design line | Light control |