



75142034

IP20



**KNX glass sensor 2gang comf, intg bus coupling unit, KNX - TS sensor, glass al.**

#### Technical properties

##### Architecture

Fixing mode flush-mounting

##### Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions, Blocking function for sensor surface e.g. for cleaning the glass surface

##### Compatibility

Extension unit extension unit for light scene push-button

##### Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

##### Dimensions

Depth 37.7 mm

Depth 5.7 mm

Dimensions (W x H x D) 86 x 160 x 5.7 mm

Height 160 mm

Width 86 mm

##### Power

Current consumption 12.5 mA

##### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

##### Screen

With display No

##### Materials

Colour of design line glass aluminium

Colour aluminium

RAL colour RAL 9006 - White aluminium

Material glass

Surface appearance glossy/matt

Type of surface treatment Tampography

**LED control**

LED with blue operation LED and 4 white status LEDs

**Installation, mounting**

Installation mode for vertical mounting

**Connection**

Bus coupling unit with integral bus coupling unit

Bus connection bus connection via connecting terminal

**Scope of delivery**

Bus connection included Yes

**Accessories included**

Matching products for glass frames in the same "style" for additional applications, see the Design line B.7, for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

**Equipment**

Number of actuation points 4

With anti-theft/dismantling protection Yes

**Use**

Differentiation characteristic 3 - Sales with integral bus coupling unit

**Use conditions**

Operating temperature -5...45 °C

Temperature temperature measurement via internal temperature sensor or external communication object, integrated temperature sensor for operation as controller extension unit, additional connection for external temperature sensor

**Identification**

Application, usage KNX - operating systems

Main design line KNX - Berker TS Sensor

Secondary design line(s) KNX, Berker TS Sensor

**Instructions**

Information text Only suitable for KNX.