



75142034

IP20



**KNX glass sensor 2gang comf, intg bus coupling unit, KNX - TS sensor, glass al.**

#### Technical properties

#### Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface

#### Compatibility

Extension unit extension unit for light scene push-button

#### Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

#### Dimensions

Depth 37.7 mm

Depth 5.7 mm

Dimensions (W x H x D) 86 x 160 x 5.7 mm

Height 160 mm

Width 86 mm

#### Power

Current consumption 12.5 mA

#### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

#### Screen

With display No

#### Materials

Colour of design line glass aluminium

Surface appearance glossy/matt

#### LED control

LED with blue operation LED and 4 white status LEDs

#### Installation, mounting

Installation mode for vertical mounting

#### Connection

Bus coupling unit	with integral bus coupling unit
-------------------	---------------------------------

Bus connection	bus connection via connecting terminal
----------------	--

---

**Scope of delivery**

Bus connection included	Yes
-------------------------	-----

---

**Accessories included**

Matching products	for glass frames in the same "style" for additional applications, see the Design line B.7 ; for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
-------------------	--

---

**Equipment**

Number of actuation points	4
----------------------------	---

With anti-theft/dismantling protection	Yes
--	-----

---

**Use**

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

---

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

---

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

Temperature	temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor
-------------	---

---

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Main design line	KNX - Berker TS Sensor
------------------	------------------------

Secondary design line(s)	KNX ; Berker TS Sensor
--------------------------	------------------------

---

**Instructions**

Information text	Only suitable for KNX.
------------------	------------------------