



75142835



KNX glass sensor 2gang comf, intg bus coupling unit, KNX-TS sensor, glass black

Technical properties

Functions	
------------------	--

With room temperature controller	Yes
	for switch, push-button, dimmer and shutter
	functions; Blocking function for sensor surface e.g.
Function	for cleaning the glass surface

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED Indication	Tes
Number of buttons	0
	operation by gently touching the sensor surfaces on
Operation	the white LED

Dimensions

Depth	37.7 mm
Depth	5.7 mm
Dimensions (W x H x D)	86 x 160 x 5.7 mm
Height	160 mm
Width	86 mm

Power

Current consumption	12.5 mA
---------------------	---------

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No

Materials

Colour of design line	glass black
Colour	black
Surface appearance	glossy/matt

LED control

LED	with blue operation LED and 4 white status LEDs
LLD	with blue operation LLD and 4 white status LLDs

Installation, mounting

Installation mode	for vertical mounting
-------------------	-----------------------

Connection	
Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
Scope of delivery	
Bus connection included	Yes
Accessories included	
Matching products	for glass frames in the same "style" for additional applications, see the Design line B.7; for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Operating temperature	-545 °C
Temperature	temperature measurement via internal temperature sensor or external communication object; integrated temperature sensor for operation as controller extension unit; additional connection for external temperature sensor
Identification Application usage	VAIV anagelia a such as
Application, usage	KNX - operating systems
Main design line	KNX - Berker TS Sensor
Secondary design line(s)	KNX ; Berker TS Sensor
Instructions	

Only suitable for KNX.

Information text