



75162592



**IP20**

## B.IQ push-button 2gang comf, KNX - B.IQ, glass black

### Technical properties

#### Functions

|                                  |    |
|----------------------------------|----|
| With room temperature controller | No |
|----------------------------------|----|

|          |   |
|----------|---|
| Function | for switch, push-button, dimmer and shutter functions |
|----------|---|

#### Compatibility

|                |  |
|----------------|--|
| Extension unit | extension unit for light scene push-button |
|----------------|--|

#### Controls and indicators

|                     |     |
|---------------------|-----|
| With LED indication | Yes |
|---------------------|-----|

|                   |   |
|-------------------|---|
| Number of buttons | 2 |
|-------------------|---|

|           |   |
|-----------|---|
| Operation | activation of second user level via object ; one push-button operation for switching, pushing, shutters and dimming |
|-----------|---|

#### Dimensions

|                   |         |
|-------------------|---------|
| Assembling height | 16.7 mm |
|-------------------|---------|

|        |         |
|--------|---------|
| Height | 88.5 mm |
|--------|---------|

|       |         |
|-------|---------|
| Width | 88.5 mm |
|-------|---------|

#### Measurement

|                   |   |
|-------------------|---|
| Value transmitter | value transmitter for dimming, position, brightness and temperature values 1 and 2 byte |
|-------------------|---|

#### Screen

|              |    |
|--------------|----|
| With display | No |
|--------------|----|

#### Materials

|                       |             |
|-----------------------|-------------|
| Colour of design line | glass black |
|-----------------------|-------------|

|        |       |
|--------|-------|
| Colour | black |
|--------|-------|

|                    |        |
|--------------------|--------|
| Surface appearance | glossy |
|--------------------|--------|

#### LED control

|     |  |
|-----|--|
| LED | with blue operation LED and 4 white status LEDs (labelling field illumination) |
|-----|--|

#### Connection

|                   |                                     |
|-------------------|-------------------------------------|
| Bus coupling unit | for bus coupling unit flush-mounted |
|-------------------|-------------------------------------|

#### Settings

|                               |            |
|-------------------------------|------------|
| Supported configuration modes | system, PB |
|-------------------------------|------------|

|                  |  |
|------------------|--|
| Parameterisation | single and two push-button operation parameterisable |
|------------------|--|

**Scope of delivery**

|                         |    |
|-------------------------|----|
| Bus connection included | No |
|-------------------------|----|

**Accessories included**

|                   |  |
|-------------------|--|
| Box               | for installation in single standard wall boxes   |
| Matching products | for glass frames in the same "style" for additional applications, see the Design line B.7 ; for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x |

**Equipment**

|  |                    |
|--|--------------------|
| Number of actuation points             | 4                  |
| With anti-theft/dismantling protection | Yes                |
| Product type:                          | product type: B.IQ |

**Safety**

|               |   |
|---------------|---|
| REACH conform | Yes   |
| RoHS conform  | Yes   |
| Protection    | with dismantling protection   |
| Alarm         | alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |

**Use conditions**

|                       |            |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

**Identification**

|                          |                             |
|--------------------------|-----------------------------|
| Application, usage       | KNX - operating systems     |
| Product family           | product family: push-button |
| Main design line         | KNX - Berker B.IQ           |
| Secondary design line(s) | KNX ; Berker B.IQ           |