



75162594



IP20

B.IQ push-button 2gang comf, KNX - B.IQ, al., al. anodised

Technical properties

Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 2

Operation activation of second user level via object ; one push-button operation for switching, pushing, shutters and dimming

Dimensions

Assembling height 16.7 mm

Height 88.5 mm

Width 88.5 mm

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of design line Aluminium

Material / workmanship aluminium, anodised

Surface appearance matt

LED control

LED with blue operation LED and 4 white status LEDs (labelling field illumination)

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

Supported configuration modes system, PB

Parameterisation single and two push-button operation parameterisable

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | No |
|-------------------------|----|

Accessories included

| | |
|-----|--|
| Box | for installation in single standard wall boxes |
|-----|--|

| | |
|-------------------|--|
| Matching products | for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x ; for aluminium frames in the same "style" for additional applications, see the Design line B.7 |
|-------------------|--|

Equipment

| | |
|----------------------------|---|
| Number of actuation points | 4 |
|----------------------------|---|

| | |
|--|-----|
| With anti-theft/dismantling protection | Yes |
|--|-----|

| | |
|---------------|--------------------|
| Product type: | product type: B.IQ |
|---------------|--------------------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
|---------------|-----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

| | |
|------------|-----------------------------|
| Protection | with dismantling protection |
|------------|-----------------------------|

| | |
|-------|---|
| Alarm | alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |
|-------|---|

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

Identification

| | |
|--------------------|-------------------------|
| Application, usage | KNX - operating systems |
|--------------------|-------------------------|

| | |
|----------------|-----------------------------|
| Product family | product family: push-button |
|----------------|-----------------------------|

| | |
|------------------|-------------------|
| Main design line | KNX - Berker B.IQ |
|------------------|-------------------|

| | |
|--------------------------|-------------------|
| Secondary design line(s) | KNX ; Berker B.IQ |
|--------------------------|-------------------|