



75164092



B.IQ push-button 4gang, KNX - B.IQ, glass black

Technical properties

| | 100 | - | Ηŝ | _ | 100 | _ |
|--|-----|---|----|---|-----|---|
| | | | | | | |

| Functions | |
|----------------------------------|--|
| With room temperature controller | No |
| Function | for switch, push-button, dimmer and shutter functions |
| Compatibility | |
| Extension unit | extension unit for light scene push-button |
| Controls and indicators | |
| With LED indication | Yes |
| Number of buttons | 4 |
| Dimensions | |
| Assembling height | 16.7 mm |
| Height | 118.1 mm |
| Width | 88.5 mm |
| Measurement | |
| Value transmitter | dimming / position value transmitter 1 byte |
| Screen | |
| With display | No |
| Materials | |
| Colour of design line | glass black |
| Colour | black |
| Surface appearance | glossy |
| Material family | Glass |
| LED control | |
| LED | with blue operation LED and 8 white status LEDs |
| Connection | |
| Bus coupling unit | for bus coupling unit flush-mounted |
| Scope of delivery | |
| Bus connection included | No |
| Accessories included | |

for installation in single standard wall boxes

for glass frames in the same "style" for additional applications, see the Design line B.7; for additional products to complement the installation in matching colours/materials, refer to the Design platform

KNX - Berker B.IQ

KNX; Berker B.IQ

Matching products

Main design line

Secondary design line(s)

| Equipment | | | |
|--|-----------------------------|--|--|
| Number of actuation points | 8 | | |
| With anti-theft/dismantling protection | Yes | | |
| Product type: | product type: B.IQ | | |
| Safety | | | |
| REACH conform | Yes | | |
| RoHS conform | Yes | | |
| Protection | with dismantling protection | | |
| Use conditions | | | |
| Operating temperature | -545 °C | | |
| Identification | | | |
| Application, usage | KNX - operating systems | | |
| Product family | product family: push-button | | |