



75664599



## B.IQ push-button 4gang thermostat, display, KNX - B.IQ, p. white, matt, plastic

### Technical properties

#### Functions

With room temperature controller	Yes
Function	with valve protection function
Timers	with room temperature timer and 2-week timer functions

#### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

#### Controls and indicators

With LED indication	Yes
Number of buttons	4
Operation	one push-button operation for switching, pushing, shutters and dimming

#### Dimensions

Assembling height	15 mm
Width of rail mounted device (RMD)	0 modules
Height	149.2 mm
Width	88.5 mm

#### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

#### Screen

With display	Yes
--------------	-----

#### Materials

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt
Material family	Plastic

#### LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	--

#### Settings

Parameterisation	single and two push-button operation parameterisable
------------------	--

**Accessories included**

Box	for installation in single standard wall boxes
-----	--

Matching products

for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x, for plastic frames in the same "style" for additional applications, see the Design line B.7

**Equipment**

Number of actuation points	10
----------------------------	----

Type of configuration	Laserdruck
-----------------------	------------

Product type:	product type: B.IQ
---------------	--------------------

Control	for individual single room temperature control
---------	--

**Software**

Update	with flash-controller technology
--------	----------------------------------

**Safety**

Protection	with dismantling protection
------------	-----------------------------

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

Energy efficiency class	IV (2%)
-------------------------	---------

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Release issue	2.6
---------------	-----

Main design line	KNX - Berker B.IQ
------------------	-------------------

Secondary design line(s)	KNX, Berker B.IQ
--------------------------	------------------