

No



80040011





Bus coupling unit flush-mtd, ext. temp. sensor, KNX

Technical properties

Controls	and	indi	cators
----------	-----	------	--------

Button / push-button with illuminated programming button

Connectivity

Interface as interface between KNX user module and bus line

Voltage

Operating voltage over bus 21...32 V DC

Electric current

Bus current consumption (data transfer) ≈ 10 mA

Dimensions

Insertion depth 32 mm

Width of rail mounted device (RMD) 0 modules

LED control

LED with red programming LED

Installation, mounting

Installation mode with spreader claws

Connection

Number of contacts 4
Bus connection bus connection via connecting terminal

Settings

Supported configuration modes system, easy

Equipment

Product type: product type: bus coupling unit

with integrated buzzer for acoustic identification of Buzzer/siren the device within the system

Use

Differentiation characteristic 3 - Sales external temperature sensor

Safety

REACH conform

RoHS conform
Yes
Halogen free
No
Protection
with dust protection flap for user interface (AST)

Use conditions		
Operating temperature	-545 °C	
Storage/transport temperature	-2070 °C (storage at > 45°C reduces the service life)	
Temperature	additional connection for external temperature sensor	
Identification		
Application, usage	KNX - system units	
Product family	product family: system components	
Main design line	KNX	