



85146179



IP20

KNX radio button 2gang quicklink, K.1, p. white glossy

Technical properties

Functions

ETS additional functions: +6 scenes, 1 button control up/down, operating mode on/off, dimming value, brightness display, push-button, status display, forced control

ETS additional functions

Configurable transmission and/or reception behaviour, reset function (to factory setting), easy additional functions: +6 scenes, on/off operating mode, 1 up/down button control

Function

Light scenes scene saving lockable

Light scenes

quicklink functions: switching, dimming, blind, 2 scenes, time switching, NO contact push-button, memory

Quicklink functions

Controls and indicators

operating areas configurable as one or two-area operation

Operation

Button / push-button with configuration and function button

Connectivity

Radio protocol KNX Radio

Receiver category 2

Receiver category

Power

Radio transmission power < 10 mW

Radio transmission power

Materials

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Material

LED control

with configuration and function LEDs, LED application module/insert compatibility display

LED

Connection

integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

Bus connection

Settings

top and bottom operating areas on 2gang switching/dimming inserts and network insert are freely configurable, toolless quicklink configuration using buttons and LED display

Programming

Equipment

Number of radio channels 4

Number of radio channels

Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %
Brightness	switch-on brightness level for each operating area on configuration with dimmer insert, power failure proof, storable
Safety	
REACH conform	No
RoHS conform	Yes
Halogen free	No
Protection	with dismantling protection
Use conditions	
Operating temperature	-5...45 °C
Energy-saving	low intrinsic energy requirement
Relative humidity (without condensation)	0...65 % (without condensation)
Identification	
Application, usage	Light control, KNX radio- operating systems
Main design line	Berker K.1
Secondary design line(s)	Berker.Net, Berker K.1