



BF341



**Earth leakage add-on block 3P 40A 300mA AC Class**

**Technical properties**

**Architecture**

Neutral position	left
Number of poles	3 P
Type of pole	3 P

**Configuration**

Number of modules	3
-------------------	---

**Main electrical features**

Rated operational voltage Ue	230 / 400 V
Frequency	50 Hz

**Voltage**

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated residual operating current	300 mA
Rated current	40 A

**Electric current / temperature**

Rating current 40°C	40 A
---------------------	------

**Dimensions**

Depth of installed product	9.2 cm
Height of installed product	7 cm
Width of installed product	3.5 cm

**Frequency**

Frequency	50 Hz
-----------	-------

**Power**

Total power loss under IN	26 W
Power loss per pole at In	8.8 W

**Tripping**

Protected against nuisance tripping	No
Short-time delayed tripping	No

**Endurance**

Electric endurance in number of cycles	2000
--	------

Number of mechanical operations	1000
---------------------------------	------

---

**Installation, mounting**

Tightening torque	2,8Nm
Type of top rail clip for modular devices	Plastic
Type of bottom rail clip for modular devices	NA
Top removability for modular devices	Yes
Bottom removability for modular devices	No

---

**Connection**

Connection cross-sect. flexible conductor	16mm <sup>2</sup>
---	-------------------

---

**Settings**

Rated fault current adjustable	No
Delay adjustable	No
Time delay of residual current	0 s

---

**Standards**

European directive WEEE	concerned
-------------------------	-----------

---

**Safety**

Protection index IP	IP20
Residual current type	AC

---

**Use conditions**

Operating temperature	-5...40 °C
Altitude	2000 m