



EGN400

## Multi-function time switch 4 channels bluetooth

### Technical properties

#### Architecture

Fixing mode DIN rail type O (symmetrical)

#### Functions

With GPS No  
hour program Yes

#### Configuration

Number of modules 4

#### Controls and indicators

Function of the pushbutton 1 way

#### Connectivity

Connection mode Radio

#### Main electrical features

Rated operational voltage  $U_e$  230 V  
Nominal voltage 230 V  
Type of supply voltage AC  
Frequency 50/60 Hz

#### Electric current

Switching current at 250 V~ 16 A

#### Dimensions

Depth of installed product 61.6 mm  
Height of installed product 90 mm  
Width of installed product 70 mm

#### Frequency

Frequency range 50...60 Hz

#### Power

Power consumed 0.71 VA  
Power consumption (operation) 500 mW

#### Lighting control

Brightness measurement range 1 / 2000 Lux

#### Fluorescent bulbs control

Max. power with fluorescent parallel lamps 400 W

Max. power fluo. duo lamp comp. series	1000 W
Compact fluorescent lamps	400 W
Fluorescent lamps parallel compensated	400 W
Max. load fluorescent lamp	400 W
<b>Incandescent bulbs control</b>	
Max. power with incandescent lamps	2300 W
230 V incandescent lamps and halogen lamps	2300 W
<b>Connection</b>	
Number of contacts	4
Type of contacts	1 changeover
Type of connection	with screw terminal
<b>Settings</b>	
Number of program steps	400
Shortest switching time	1 mn
Annual program	Yes
Astro program	Yes
Daily program	Yes
Weekly program	Yes
<b>Scope of delivery</b>	
Memory card included	No
<b>Equipment</b>	
Pulse duration for inputs	1 s
Number of channels	4
Number of switching times for on/off	400
Supply failure reserve	10 years
Summer-/winter switchover	Yes
With cyclic program	Yes
With holidays program	No
With Impulse program	Yes
With preset programm	Yes
With random program	No
<b>Use</b>	
Local operation/hand operation	Yes
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	
Working accuracy	60
Relative humidity	95 %