



FB6013007030



Trunking 60x130, grey

Technical properties

Configuration

Antibacterial treatment	No
-------------------------	----

Compatibility

Device installation compatible format	Standard 60mm, CEE, MCBs
---------------------------------------	--------------------------

Connectivity

Trunking coupling	without coupler
-------------------	-----------------

Dimensions

Trunking height	61 mm
Length	2000 mm
Trunking width	130 mm

Capacity

Maximum number of cables (Ø 11 mm, 50% fill)	27
Maximum number of cables (Ø 11 mm, 50% fill)	27

Cover, door

Lid mounting	External
Lid shape	loose
Lid width	130 mm
Number of lids mountable	1

Materials

Material group	plastic
Type of surface treatment	untreated
Transparent	No

Installation, mounting

Base punching	With base punching
---------------	--------------------

Cable

Internal/useful cross section	6450 mm ²
-------------------------------	----------------------

Equipment

Number of plugable separators	1
Compartment quantity	1 / 2
Cable retainers per meter	2

Standards

European directive RoHS

voluntary compliance

Safety

REACH conform

No

RoHS conform

Yes

Halogen free

No

Impact strength

IK07

Use conditions

Operating temperature

-5...60 °C

temperatur

Ambient temperature

-5...65 °C