



FU62AN

Enclosure, NewVegaD, 1137x550x182mm, 144 modules, flush-mounted, to complete

Technical properties

| Co | nfia | uration | |
|----|------|---------|--|
| | | | |

| Module | with terminals |
|-------------------|----------------|
| Number of modules | 144 |
| | |

Electric current

| Rated current | 160 A |
|---------------|-------|

Dimensions

| Depth of installed product Internal depth Height of installed product Installation height Width of installed product Width in division units Thickness of sidewall material | |
|---|---------|
| Internal depth Height of installed product Installation height Width of installed product Width in division units Thickness of sidewall material | 110 mm |
| Height of installed product Installation height Width of installed product Width in division units Thickness of sidewall material | 182 mm |
| Installation height 1: Width of installed product Width in division units Thickness of sidewall material | 110 mm |
| Width of installed product Width in division units Thickness of sidewall material | 1137 mm |
| Width in division units Thickness of sidewall material | 1137 mm |
| Thickness of sidewall material | 600 mm |
| | 24 |
| Built-in width | 1 mm |
| | 550 mm |

Cover, door

| Cover type | With Notch |
|---------------------------|---------------|
| Door locking | without |
| Door leave | single |
| Cover type | none / closed |
| Transparent cover or door | No |

Materials

| Colour | white |
|---------------------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
| Type of surface treatment | powder-coated |

Installation, mounting

| Suitable for outdoor use | No |
|--------------------------|----|
| | |

Connection

| Number of conduit inlets | 4 |
|--------------------------|---|
|--------------------------|---|

Settings

| Enclosure type | Distributor empty cabinet |
|----------------|---------------------------|

Equipment

| Number of rows | 6 |
|----------------|---|

| Quantity of section in width | 2 |
|--------------------------------------|---------------|
| Quantity of rails | 4 |
| Can be accessorized | Yes |
| Number of openings for flange plates | 2 |
| Extension possible | No |
| Earthing terminal block | No |
| Neutral terminal block | No |
| Signal passing door | No |
| Standards | |
| European directive WEEE | not concerned |
| Safety | |
| Protection class | isol.class II |
| REACH conform | No |
| RoHS conform | Yes |
| Halogen free | No |