



HAD312

**Load break switch 3P 125A**

**Technical properties**

**Architecture**

Number of poles	3 P
Type of case	Fixed built-in

**Functions**

Reversing switch	No
------------------	----

**Configuration**

Number of modules	4.45
-------------------	------

**Controls and indicators**

Motor drive integrated	No
------------------------	----

**Main electrical features**

Rated operational voltage Ue	380 / 415 V
------------------------------	-------------

**Voltage**

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V

**Electric current**

Rated operational current in AC21 category B	125 A
Rated current	125 A
Short-circuit current with gI-gG fuses	25 kA
Rated short-time withstand current 1s	2.75 kA
Acceptable current rating with AC22 category B	125 A
Rated operational current in AC23 category A	100 A
Acceptable current rating with AC23 category B	100 A

**Power**

Total power loss under IN	21.3 W
Power loss per pole at In	7.1 W
Contact rating with 400 V in AC1	82 kW

**Cover, door**

Interlockable	Yes
---------------	-----

**Equipment**

Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Width available for insulation connection	95 mm <sup>2</sup>
Motor drive optional	No

#### **Standards**

European directive WEEE	concerned
-------------------------	-----------

#### **Safety**

Protection index IP	IP20
---------------------	------

#### **Use conditions**

Operating temperature	-20...70 °C
-----------------------	-------------