



HI456

Change-over switch 4P 400A

Technical properties

Arc	h	it	ec	tu	re
-----	---	----	----	----	----

Type of order	Long thumb-grip
Number of poles	4 P
Type of pole	4 P
Type of case	Fixed built-in
Functions	
Reversing switch	Yes
Controls and indicators	
Motor drive integrated	No
Main electrical features	
Rated operational voltage Ue	380 / 400 / 500 / 690 V
Frequency	50/60 Hz
Voltage	
Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V
Rated operational voltage in DC	260 / 400 / 500 V
Electric current	
Rated operational current in AC21category B	400 A
Acceptable current rating with AC22 category A	400 A
Rated current	400 A
Short-circuit current with gl-gG fuses	50 kA
Rated short-time withstand current 1s	8 kA
Thermal rated current outside of housings	400 A
Rated operational current in AC21 category A	400 A
Acceptable current rating with AC22 category B	400 A
Rated operational current in AC23 category A	400 A
Acceptable current rating with AC23 category B	400 A
Power	
Nominal power under 440/500, 50Hz	160 kW

Active power under 380/415 V, 50 Hz	220 kW
Total power loss under IN	43.2 W
Power loss per pole at In	15.1 W
Contact rating with 400 V in AC1	263 kW
Endurance	
Electrical durability at nominal load in AC21in operating cycles	1000
Electrical durability at nominal load in AC22 in operating cycles	200
Number of mechanical operations	10000
Cover, door	
Interlockable	Yes
Connection	
Connection cross-sect. rigid cable	185 / 240mm²
Type of connection	Terminal
Equipment	
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change- over contact	0
Motor drive optional	No
Standards	
Standard text	IEC 60947-3
Safety	
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Air humidity protection	yes according to IEC 68-2-30