

KDN163A

Insulated busbar 1P 63A fork 10mm² 12M

Technical properties

Number of poles	1 P
Type of pole	1 F
Compatibility	
Intended for the compatible references	Modular devices
Main electrical features	
Rated operational voltage Ue	415 V
Voltage	
Max operating voltage	230 V
Electric current	
Rated current	63 A
Dimensions	
Length	210 mm
Pitch	17.8 mm
Installation, mounting	
	Να
Suitable to a device with an auxiliary	No
Suitable to a device with an auxiliary Connection	
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable	10mm
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar	10mm No
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type	10mm No busbar fork
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type	10mm No busbar fork
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type Type of connection Equipment	10mm No busbar fork with screw / quick connect
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type Type of connection Equipment Number of appliances to build in	10mm No busbar fork with screw / quick connect
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type Type of connection Equipment Number of appliances to build in Safety	10mm No busbar fork with screw / quick connect 12
Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type Type of connection Equipment Number of appliances to build in Safety REACH conform	10mm No busbar fork with screw / quick connect 12
Installation, mounting Suitable to a device with an auxiliary Connection Connection cross-sect. rigid cable Suitable for product with neutral busbar Connector type Type of connection Equipment Number of appliances to build in Safety REACH conform RoHS conform Use conditions	No 10mm No busbar fork with screw / quick connect 12 No Yes