



MU210A

MCB 2P 6kA C-10A 2M

Technical properties

		_	_			
- ^	200	h	54.	~	. 4	ire

Neutral position	without neutral
Number of poles	2 P
Type of pole	2 P
Curve	С
Functions	
Concurrently switching N-neutral	No
Configuration	
Number of modules	2
Connectivity	
Top connection alignement for modular devices	Aligned terminal
Bottom connection alignement for modular devices	Aligned terminal
Main electrical features	
Rated operational voltage Ue	400 V
Type of supply voltage	AC
Voltage	
Rated insulation voltage	500 V
Max operating voltage	415 V
Rated impulse withstand voltage	4000 V
Electric current	
Rated current	10 A
min/maxi threshold value of the AC thermal operation	1.13 / 1.45 ln
Magnetic regulating currrent	5 / 10 In
Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1	6 kA
Rated short circuit breaking capacity Icn under 400V AC according IEC60898-1	6 kA
Electric current / temperature	
Rating current -25°C	13.4 A
Rating current -20°C	13.1 A
Rating current -15°C	12.8 A
Rating current -10°C	12.54 A

Rating current -5°C	12.21 A
Rating current 0°C	11.91 A
Rating current 5°C	11.61 A
Rating current 10°C	11.31 A
Rating current 15°C	11.01 A
Rating current 20°C	10.72 A
Rating current 25°C	10.42 A
Rating current 30°C	10 A
Rating current 35°C	9.82 A
Rating current 40°C	9.52 A
Rating current 45°C	9.22 A
Rating current 50°C	9 A
Rating current 55°C	8.63 A
Rating current 60°C	8.33 A
Rating current 65°C	8.03 A
Rating current 70°C	7.73 A
Current correction factors	
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3	0.95
<u> </u>	0.95
devices placed side-by-side Correction factor of rating current for 4 and	
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6	
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6	0.9
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions	0.9
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product	0.9 0.85 70 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product	0.9 0.85 70 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product	0.9 0.85 70 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to	0.9 0.85 70 mm 35 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side	0.9 0.85 70 mm 35 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard	0.9 0.85 70 mm 35 mm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance	0.9 0.85 70 mm 35 mm 3 W 1.57 W
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles	0.9 0.85 70 mm 35 mm 3 W 1.57 W
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles	0.9 0.85 70 mm 35 mm 3 W 1.57 W
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations	0.9 0.85 70 mm 35 mm 3 W 1.57 W
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting	0.9 0.85 70 mm 35 mm 3 W 1.57 W
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting Type of top connection for modular devices	0.9 0.85 70 mm 35 mm 3 W 1.57 W 4000 20000
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting Type of top connection for modular devices Tightening torque	0.9 0.85 70 mm 35 mm 3 W 1.57 W 4000 20000 with screw 2,8Nm
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting Type of top connection for modular devices Tightening torque Type of top rail clip for modular devices	0.9 0.85 70 mm 35 mm 3 W 1.57 W 4000 20000 with screw 2,8Nm NA
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting Type of top connection for modular devices Tightening torque Type of bottom rail clip for modular devices Type of Bottom Connection for modular	0.9 0.85 70 mm 35 mm 3 W 1.57 W 4000 20000 with screw 2,8Nm NA metallic
devices placed side-by-side Correction factor of rating current for 4 and 5 devices placed side-by-side Correction factor of rating current for 6 devices placed side-by-side Dimensions Depth of installed product Width of installed product Power Maximum power loss per pole according to the product standard Power loss per pole at In Endurance	0.9

Connection cross-section at output with screw, for flexible conductor	1 / 25 mm²
Connection cross-section at output with screw, for massive conductor	1 / 35 mm²
Connection cross-section for rigid conductor, upstream terminals with screws	1 / 35 mm²
Connection cross-section of the access with screws, with flexible conductor	1 / 25 mm²
Downstream cage clamp delivery status	opened
Upstream cage clamp delivery status	opened
Type of connection	with screw
Equipment	
Can be accessorized	Yes
With transparent product label holder	No
Standards	
Standard text	IEC 60898-1
Safety	
REACH conform	No
RoHS conform	Yes
Halogen free	No
Use conditions	
Operating temperature	-2570 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I²t	3
Altitude	2000 m
Storage/transport temperature	-2580 °C
temperatur	
Temperature of calibration	30 °C