



TRC270D



Plug adaptor radio, ON/OFF, 10/16A, SCHUKO

Technical properties

Architecture

Fixing mode	pluggable
-------------	-----------

Functions

ETS additional functions	ETS additional functions: +6 scenes, operating mode on/off, forced control, status display
Quicklink functions	quicklink functions: switching, 2 scenes, time switching, NO contact push-button

Configuration

Number of modules	0
-------------------	---

Controls and indicators

Indicator lamp	yes
----------------	-----

Connectivity

Radio protocol	KNX Radio
Receiver category	2

Main electrical features

Frequency	50 Hz
-----------	-------

Voltage

Operating voltage over bus	21...32 V DC
----------------------------	--------------

Electric current

Number of entry circuits	0
Maximum through current	16 A
Switching current	max. 16 A

Dimensions

Depth	77 mm
Assembling height	41 mm
Height	54 mm
Width	98 mm

Frequency

Radio reception frequency	868.3 MHz
---------------------------	-----------

Power

Output power	3680 W
Conventional transformers	1600 VA

Electronic transformers and dual-mode transformers	1200 W
--	--------

Materials

Colour of design line	polar white
Surface appearance	matt

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
230 V incandescent lamps and halogen lamps	2300 W

Settings

Supported configuration modes	system, PB
-------------------------------	------------

Scope of delivery

Bus connection included	No
-------------------------	----

Equipment

Number of outputs	1
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %

Use conditions

Operating temperature	0...45 °C
Storage/transport temperature	-20...70 °C
Relative humidity (without condensation)	0...65 % (without condensation)