



TXA215

Dimmer 1 channel 1000W

Technical properties

Architecture

Bus system KNX

Functions

Bus module detachable No

Multi-phase mode suitable to switch different external conductors

Soft startup bulb-preserving soft startup

Configuration

Number of modules 6

Controls and indicators

With LED indication Yes

Indicator lamp yes

Operation manual operation also possible without bus, e.g. on building site ; Manual operation can be activated via selection switch, thereby deactivation of the KNX function ; Manual operation per channel via button with integrated status LED, thereby lockout of KNX function

Indication / display LC display with illumination ; status LED integrated in the manual operation button

Manual selection switches / push-buttons selection switch for manual/bus operation as well as load setting

Button / push-button with illuminated programming button

Main electrical features

Frequency 50/60 Hz

Rated current 4.3 A

Voltage

Auxiliary voltage 230 V AC

Input voltage 230 V AC

Operating voltage over bus 21...32 V DC

Electric current

Bus current consumption (data transfer) 2.3 mA

Fuse

Fuse short-circuit proof and overload proof (display using LEDs) ; overheating protection (display using LEDs)

Dimensions

Width of rail mounted device (RMD) 6 modules

Power	
Dimmable conventional transformers	20...1000 VA
Incandescent bulb power	20 / 1000 W
Total power loss under IN	10 W
Electronic transformers	20...1000 W
Power supply	
Supply voltage	230 V AC
LED control	
LED	Status LED integrated in manual operation button ; Overheating protection, display using LEDs ; Overload protection, display via LED
Incandescent bulbs control	
230 V incandescent lamps and halogen lamps	20...1000 W
Connection	
Connection cross-sect. flexible conductor	0,75 / 2,5mm ²
Connection cross-sect. rigid cable	0,75 / 2.5mm ²
Type of load	universal
Conductor cross-section (flexible)	0.75...2.5 mm ²
Conductor cross-section (rigid)	0.75...2.5 mm ²
Bus coupling unit	with integral bus coupling unit
Type of connection	with QuickConnect plug-in terminals
Bus connection	bus connection via connecting terminal
Type of connection	quick connect
Settings	
Supported configuration modes	system
Parameterisation	parameter definable behaviour in the event of bus voltage failure/return
Scope of delivery	
Bus connection included	Yes
Equipment	
Type of dimmer	universal
Modular expandability	No
Dimming principle	phase cut-on or cut-off according to load type, self-learning ; minimum/maximum dimming values per channel settable on device
low noise	very low noise
Use	
Local operation/hand operation	Yes
Safety	
Protection	with overheating, overload and short-circuit protection
Use conditions	

Operating temperature 0...45 °C

Storage/transport temperature -20...60 °C

Identification

Main design line KNX