



TXB602F



**Output module 2x 6A /230V~, flush mounted, KNX**

**Technical properties**

**Architecture**

Number of blinds/shutters outputs	1
Fixing mode	flush-mounting

**Configuration**

Number of modules	0
-------------------	---

**Controls and indicators**

Indicator lamp	yes
----------------	-----

**Main electrical features**

Rated operational voltage Ue	230 V
Rated current	6 A

**Voltage**

Max. switching capacity at	230 V AC
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

**Electric current**

Bus current consumption (data transfer)	7 mA
Bus current consumption (idle)	5 mA
Number of entry circuits	0
Maximum switching current	6 A
Maximum through current	6 A
Rated current	6 A
Switching current at $\cos \varphi = 0.8$	max. 6 A
Withstand current in AC1 for the contact path or zone 1	6 A

**Dimensions**

Height of installed product	44 mm
Dimensions (LLxwwxhh)	44 x 43 x 22 mm
Width of rail mounted device (RMD)	0 modules
Height	44 mm

**Power**

Max. power with electronic transfo.	500 W
Total power loss under IN	0.5 W
Output power	500 W
Max. switching power	1200 W

Conventional transformers	500 VA
Electronic transformers	500 W
<b>Measurement</b>	
Input scanning voltage	12 V DC V DC
<b>Materials</b>	
Colour	light grey
<b>Lighting control</b>	
Fluorescent lamps with electronical ballast (EB)	6 x 48 W
- uncompensated	500 VA
<b>Fluorescent bulbs control</b>	
Energy-saving lamps	13 W
Power lighting fluo lamps	5 x 13W
Max. power fluo. duo lamp comp. series	6 x 48W
<b>LED control</b>	
Max number of LED/CFL lamps	5
Power LED	65 W
<b>Incandescent bulbs control</b>	
Max. power with incandescent lamps	500 W
230 V incandescent lamps and halogen lamps	500 W
<b>Connection</b>	
Conductor cross-section (flexible)	0.75...2.5 mm <sup>2</sup>
Conductor cross-section (rigid)	0.75...2.5 mm <sup>2</sup>
Number of contacts	2
Bus coupling unit	with integral bus coupling unit
Type of connection	with screw terminals
<b>Settings</b>	
Supported configuration modes	system
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Equipment</b>	
Number of outputs	2
Modular expandability	No
<b>Use</b>	
Differentiation characteristic 3 - Sales	with screw terminals
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	

Operating temperature -5...45 °C

Storage/transport temperature -20...70 °C

---

**Identification**

Main design line KNX