


TYA664A



## DIMMER 4 CHANNELS 300W

### Technical properties

#### Architecture

Bus system	KNX
Fixing mode	REG

#### Functions

Bus module detachable	No
Multi-phase mode	suitable to switch different external conductors
Soft startup	bulb-preserving soft startup

#### Configuration

Number of modules	8
-------------------	---

#### Controls and indicators

With LED indication	Yes
Indicator lamp	yes
Operation	manual operation also possible without bus, e.g. on building site
Manual selection switches / push-buttons	selection switch for manual/bus operation as well as load setting
Button / push-button	with illuminated programming button

#### Main electrical features

Frequency	50/60 Hz
Rated current	5.2 A

#### Voltage

Auxiliary voltage	230 V AC
Input voltage	230 V AC
Operating voltage over bus	21...32 V DC

#### Electric current

Bus current consumption (data transfer)	< 2.3 mA
---	----------

#### Fuse

Fuse	overheating protection (display using LEDs)
------	---

#### Dimensions

Width of rail mounted device (RMD)	8 modules
------------------------------------	-----------

#### Power

Dimmable conventional transformers	per channel 300 VA
Incandescent bulb power	20 / 300 W

Total power loss under IN	1.71 W
Electronic transformers	per channel 300 W
<b>Power supply</b>	
Supply voltage	230 V +10% / -15%
<b>Materials</b>	
Colour	RAL 7035
<b>Fluorescent bulbs control</b>	
Dimmable energy-saving lamps	per channel 60 W
Power lighting fluo lamps	4 x 60W
<b>LED control</b>	
Quantity of dimmable, 230 V retrofit LED lamps	per channel max. 8
Max number of LED/CFL lamps	8
Dimmable LED lamps	per channel 60 W
Dimmable 230 V retrofit LED lamps	per channel 60 W
Power LED	60 W
<b>Incandescent bulbs control</b>	
Max. power with incandescent lamps	300 W
230 V incandescent lamps and halogen lamps	per channel 300 W
<b>Connection</b>	
Type of load	universal
Conductor cross-section (flexible)	0.75...2.5 mm <sup>2</sup>
Conductor cross-section (rigid)	0.75...2.5 mm <sup>2</sup>
Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
Type of connection	quick connect
<b>Settings</b>	
Supported configuration modes	system
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Equipment</b>	
Type of dimmer	universal
Modular expandability	No
Dimming principle	phase cut-on or cut-off according to load type, self-learning
low noise	very low noise
<b>Use</b>	
Local operation/hand operation	Yes
<b>Safety</b>	
Protection index IP	IP20

**Use conditions**

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C

**Identification**

Main design line	KNX
------------------	-----