



TYMS646T



## Heating actuator 6 channels KNX 24/230V

### Technical properties

#### Architecture

Bus system KNX

#### Functions

Multi-phase mode for 1 phase operation

#### Configuration

Number of modules 4

#### Controls and indicators

Button / push-button with programming button and red programming LED

#### Main electrical features

Frequency 50/60 Hz

#### Voltage

Auxiliary voltage 110...230 V AC

Operating voltage over bus 21...32 V DC

Switching voltage 24...230 V

#### Materials

Colour independent of design lines light grey

RAL colour RAL 7035 - Light grey

#### Connection

Conductor cross-section (flexible) 0.5...4 mm<sup>2</sup>

Conductor cross-section (rigid) 0.5...4 mm<sup>2</sup>

Bus coupling unit with integral bus coupling unit

Bus connection bus connection via connecting terminal

#### Settings

Supported configuration modes system

#### Scope of delivery

Bus connection included Yes

#### Equipment

Modular expandability No

Actuators, 24 V per channel max. 2

Actuators per channel max. 4

#### Use

**Safety**

---

REACH conform	No
RoHS conform	Yes
Halogen free	No

**Use conditions**

---

Storage/transport temperature	-20...70 °C
-------------------------------	-------------

**Identification**

---

Main design line	KNX
------------------	-----