



WNE040B

cubyko 2-gang 2-way switch flush mounted white IP55

Technical properties

Architecture

Type of order	Switch
Type of control unit	double rocker

Configuration

Switch mode	2 way
-------------	-------

Controls and indicators

Indicator lamp	as an accessory
Push-buttons	No

Main electrical features

Nominal voltage	250 V
Frequency	50/60 Hz

Electric current

Rated current	10 AX
---------------	-------

Dimensions

Depth of installed product	40 mm
Height of installed product	75 mm
Dimensions (LLxwwxhh)	83X83X37
Width of installed product	75 mm

Capacity

Number of modules for WA	2
--------------------------	---

Materials

RAL colour	RAL 9010 - Pure white
Material	polypropylène

Installation, mounting

Mounting type	flush
---------------	-------

Connection

Connection cross-sect. rigid cable	mini 2x1 mm ² - maxi 2x2,5 mm ²
Type of contacts	2 way
Type of connection	Quickconnect

Equipment

Lighting	without lighting (cannot be illuminated)
----------	--

Heating switch No

Standards

Approvals EN 60669-1

Safety

IK protection code against mechanical impacts 07

REACH conform Yes

RoHS conform Yes

Halogen free Yes

Impact strength IK07

Use conditions

Operating temperature -15...30 °C

Storage/transport temperature -50...50 °C

Identification

Range cubyyko

Composition Mechanism with upper casing