

250 V

-10...35 °C



WXF100

Socket gallery 2P+E

Technical properties

Nominal voltage

Materials

| Architecture | |
|---------------|---------|
| Type of order | Socket |
| Fixing mode | Clipped |

| Configuration | |
|-------------------|---|
| Number of modules | 2 |

| Main electrical features | | |
|--------------------------|--|--|

| Dimensions | |
|------------|----------|
| Depth | 35.65 mm |

| -1- | |
|--------|-------|
| Height | 45 mm |
| Width | 45 mm |

| Materials | |
|--------------------|--------------------|
| Material | Polycarbonate (PC) |
| Surface appearance | matt |

| Type of surface treatment | untreated |
|---------------------------|-----------|
| | |

| Connection | |
|---|--------------|
| Connection cross-sect. flexible conductor | 1,5 / 2,5mm² |

| Connection cross-sect. rigid cable | 1,5 / 2,5mm ² |
|------------------------------------|--------------------------|

| Equipment | |
|---------------------------------------|----|
| With transparent product label holder | No |

| Standards | |
|-------------------------|-----------|
| European directive WEEE | concerned |

| European ancetive WEEE | concerned |
|--|-----------|
| Safety | |
| IK protection code against mecanical impacts | 05 |
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | No |
| | |

| Protection | Enhanced contact protection |
|----------------|-----------------------------|
| Use conditions | |

| Storage/transport temperature | -1050 °C |
|-------------------------------|----------|

Operating temperature

 Identification

 Composition
 Middle plate