

Enhanced contact protection



WXF421E

Socket for trunking gallery 2P+E 16A orange

Technical properties

| Architecture | |
|--|-------------------------------|
| Type of order | Socket |
| Type of pole | 2P+T |
| Configuration | |
| Number of modules | 3 |
| Main electrical features | |
| Nominal voltage | 250 V |
| Electric current | |
| Rated current | 16 A |
| Dimensions | |
| Depth | 45 mm |
| Height | 43.5 mm |
| Width | 67.5 mm |
| Cover, door | |
| Cover | Complete housing |
| Materials | |
| Surface appearance | glossy |
| Type of surface treatment | untreated |
| Connection | |
| Connection cross-sect. flexible conductor | 1,5 / 2,5mm² |
| Connection cross-sect. rigid cable | mini 2x1 mm² - maxi 2x2,5 mm² |
| Type of connection | Quickconnect |
| Equipment | |
| With transparent product label holder | No |
| Standards | |
| Approvals | NFC 61314 |
| Safety | |
| IK protection code against mecanical impacts | 07 |
| | |

Use conditions

Protection

| Operating temperature | -1035 °C |
|-------------------------------|----------|
| Storage/transport temperature | -1050 °C |

Mechanism with upper casing

Identification
Composition