



WXF436T

**Switch 16AX multi sockets Gallery 2P+E titane**

**Technical properties**

**Architecture**

Type of order	Switch
Type of pole	2P+T
Type of control unit	single rocker
Fixing mode	Clipped

**Configuration**

Antibacterial treatment	No
-------------------------	----

**Compatibility**

IFTTT support available	No
-------------------------	----

**Main electrical features**

Nominal voltage	250 V
Frequency	50/60 Hz

**Electric current**

Rated current	16 AX
---------------	-------

**Dimensions**

Depth	52 mm
Insertion depth	52 mm
Height	45 mm
Width	45 mm

**Materials**

Free area for finishing name	titane
Surface appearance	satin finish
Type of surface treatment	untreated

**Connection**

Connection cross-sect. flexible conductor	0,5 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,5 / 2,5mm <sup>2</sup>
Type of connection	Quickconnect

**Equipment**

With transparent product label holder	No
---------------------------------------	----

**Standards**

Approvals	EN 60669-1
-----------	------------

**Safety**

---

IK protection code against mechanical impacts

05

**Use conditions**

---

Operating temperature

-10...35 °C

Storage/transport temperature

-10...50 °C

**Identification**

---

Range

gallery

Composition

Mechanism with upper casing