



EV charging station witty park 1x22kW 3P M3T2S IP54 RFID

Technical properties

Connection system	Typ 2
Functions	
Function access control	Yes
With load management	Yes
Connectivity	
Number of charging points	1
Number of CEE socket outlets	0
Number of socket outlets GB	0
Number of socket outlets Type 2	1
Number of socket outlets Type 3	0
Number of vehicle connectors CHAdeMO	0
Number of vehicle connectors Type 1	0
Number of vehicle connectors Type 1 CCS	0
Number of vehicle connectors Type 2	0
Number of vehicle connectors Type 2 CCS	0
Main electrical features	
Nominal voltage	230/400 V
Frequency	50 Hz
Rated current	32 A
Dimensions	
Depth of installed product	233 mm
	233 mm 480 mm
Depth of installed product	
Depth of installed product Height of installed product	480 mm
Depth of installed product Height of installed product Length	480 mm
Depth of installed product Height of installed product Length Width of installed product	480 mm
Depth of installed product Height of installed product Length Width of installed product Power	480 mm 480 mm 346 mm
Depth of installed product Height of installed product Length Width of installed product Power connected load	480 mm 480 mm 346 mm
Depth of installed product Height of installed product Length Width of installed product Power connected load Max. power per charging point	480 mm 480 mm 346 mm 22 kW 22 kW
Depth of installed product Height of installed product Length Width of installed product Power connected load Max. power per charging point Power supply	480 mm 480 mm 346 mm 22 kW 22 kW
Depth of installed product Height of installed product Length Width of installed product Power connected load Max. power per charging point Power supply Number of phases for the power supply	480 mm 480 mm 346 mm

Material group	other
Equipment	
With energy meter	No
With house connection box	No
Number of household socket outlets	0
Number of vehicle connectors GB AC	0
Number of vehicle connectors GB DC	0
With circuit breaker	No
Standards	
European directive RoHs	compliant
Safety	
Protection index IP	IP54
REACH conform	No
Halogen free	No
Impact strength	IK10