



14057003

Rocker, K.5, al., al. anodised

Technical characteristics

Controls and indicators

| | |
|----------------------------------|-----------------------------------------------------------------------------|
| Push-buttons | also for KNX applications: push-button, 1gang, and group push-button, 1gang |
| Rocker switch/rocker push-button | for rocker push-buttons ; for change-over/intermediate switch |

Materials

| | |
|------------------------|---------------------|
| Colour of design line | Aluminium |
| Material / workmanship | aluminium, anodised |
| Surface appearance | matt |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Use cases

| | |
|-------------|---------------|
| Application | Light control |
|-------------|---------------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | Yes |

Identification

| | |
|--------------------|-------------------------------------------------------------------------------|
| Application, usage | KNX - operating systems ; Flush-mounted wet-room installation ; Light control |
| Main design line | Berker K.5 |

Instructions

| | |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special note text | these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44"). |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|