



14157104

Rocker, lab. field, lens, K.5, stainless steel, metal matt finish

Technical characteristics

Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang
Rocker switch/rocker push-button	for rocker push-buttons, for change-over/intermediate switch

Materials

Colour of design line	Stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal, matt finish
Material	stainless steel
Surface appearance	matt

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Equipment

Lighting	for lighting and monitoring circuit
----------	-------------------------------------

Use cases

Application	Light control
-------------	---------------

Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	Lens

Identification

Application, usage	Light control, Flush-mounted wet-room installation
Main design line	Berker K.5

Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
Information text	For labelling with names, notes etc. Labelling field height designed for 6 mm P-touch strip.